



AQM

SERIES

THE EASYWEIGHER





AQM

FEATURES

- OIML-R76 and EC Class III Type Approved
- Extended Display Function Provides 1/30000 Display Resolution when Required*
- Support Metric and Avordupois Weight Units and Conversion
- User Friendly Operation
- Equipped with Power On Zero Tracking, Manual Zero, Auto Calibration, Smart Power Saving and Automatic Tare Functions
- Wide Angle LCD Display Digits
- Protection Devices against Overload and Shock
- Dual Power Source: By Built-in Rechargeable Battery or Power Adapter
- Long Battery Operating Time: 120 Hours Plus
- Adjustable Feet, Built-in Rechargeable Battery, Power Adapter and Bubble Level Included

*Extended Display Function does not support avordupois weight units

OPTIONS AVAILABLE

- Rear Display
- All Stainless Steel Platter Cover

SPECIFICATIONS

Model No.	Capacity	Division	
		OIML	Extended
AQM-1500	1500g	0.5g	0.05g
AQM-3000	3000g	1g	0.1g
AQM-6000	6000g	2g	0.2g
Tare Range	Full Tare Range (Subtractive)		
Platter	170 x 200mm ABS		
Power Source	Built-in Rechargeable Battery or External AC/DC Power Adapter		
Operation Environment	0°~40°C (32°~104°F), Non-condensed, R.H. ≤ 85%		

* Specifications subject to change without notice



UNIVERSAL WEIGHT ENTERPRISE CO., LTD.

2-5 Floor No. 30 Pao Shing Road Hsin Tian City 831 Taipei Hsien Taiwan R.O.C.
Tel: +886-2-29100121 (12 Lines) Fax: +886-2-29101500 • 29100652 • 2912170-7
<http://www.uwe-scales.com.tw> e-mail: uwe@msl.hinet.net

Mar '2003 Designed by DAILY
Printed in Taiwan