



VGW

PRODUCT INFORMATION

- ✓ OIML R76:2006 approved dual weighing range
- ✓ High speed 24 bits A/D converters for performance and stability
- ✓ Simple piece counting
- ✓ Alarm for check weighing function
- ✓ Wide angle LCD display with LED backlight
- ✓ Overload and shock protection mechanism protects against excessive loads and shock
- ✓ Easy grip design for mobility convenience
- ✓ Functions including: power on zero tracking, manual zero, dual weighing range, full subtractive tare, memory accumulation, kg/lb conversion, auto power saving, low battery warning and charging status indicator
- ✓ Features including: backlight, platter with SUS304 insert, rechargeable battery, power adaptor, adjustable feet
- ✓ Battery operation time: 200 hours plus
- ✓ Pan size: 230 x 250 mm
- ✓ Options available: RS-232 interface

3 color backlight for checkweighing



Model	Capacity	Readability
VGW-3	3 kg	0.1 g
VGW-6	6 kg	0.2 g
VGW-15	15 kg	0.5 g
VGW-30	30 kg	1 g



UNIVERSAL WEIGHT ELECTRONICS CO., LTD.

4th FLOOR, NO.53, BAOXING ROAD, XINDIAN DISTRICT, NEW TAIPEI CITY 231, TAIWAN (R.O.C)

+886-2-29180121 | int@uwe.com.tw | www.uwe.com.tw